



Rotating rotor blade of a wind turbine

ImageIR® 8800

Long Wave Thermography Camera with Shortest Integration Times

**640
x
512**
Detector

Detector Format
Large detector enables
highest sensitivity

1.3
MegaPixel

MicroScan
(1,280 x 1,024) IR pixels by
genuine camera hardware

**640
x
512**
233 Hz

IR-Frame Rate
Analysis of extreme temperature
changes and gradients in full frame

**±1
%**

Measurement Accuracy
Highly accurate and
repeatable measurements

T_{int}

Shortest Integration Time
Accurate temperature measurements
of fast processes

**10
GigE**

10 GigE Interface
High-speed, long-distance interference
proof data transmission

LWIR

Spectral Range
Measurement in the range
of (7.7 ... 10.2) μm

With its ImageIR® 8800 InfraTec offers another top-level thermographic camera model from the ImageIR® high-end camera series. It is equipped with a cooled focal-plane array photon detector that provides a format of (640 x 512) IR pixels and operates in snapshot mode. This camera combines an outstanding thermal resolution – better than 0.025 K – with very high sub-frame rates of up to 14,593 Hz and extremely short integration times of only a few microseconds. Thereby it qualifies for airborne biological and geological surveys, non-destructive testing and the analysis of fast thermal processes, which are related to large temperature measuring ranges. Its modular structure, which consists of optical, detector and interface modules, makes it easily adaptable to the respective application.

An integrated trigger interface guarantees a repeatable high-precision triggering of quick procedures. Multiple configurable digital in- and outputs serve as control ports for the camera or as a generator of control signals for external devices. The optical channel consists of exchangeable infrared lens systems as well as of application-specific apertures, filters and optical elements.

Technical Specifications

Spectral range	(7.7 ... 10.2) μm
Pitch	15 μm
Detector	MCT
Detector format (IR pixels)	(640 \times 512)
Image format with opto-mechanical MicroScan (IR pixels)*	(1,280 \times 1,024)
Image acquisition	Snapshot
Readout mode	ITR
Aperture ratio	f/2.0
Detector cooling	Stirling cooler
Temperature measuring range	(-40 ... 1,700) $^{\circ}\text{C}$, up to 3,000 $^{\circ}\text{C}$ *
Measurement accuracy	± 1 $^{\circ}\text{C}$ or ± 1 %
Temperature resolution @ 30 $^{\circ}\text{C}$	Better than 0.025 K
Frame rate (full / half / quarter / sub frame)*	Up to 233 / 874 / 2,892 / 14,593 Hz
Window mode	Yes
Focus	Manually, motorised or automatically*
Dynamic range	Up to 16 bit*
Integration time	(10 ... 20,000) μs
Rotating aperture wheel and filter wheel*	Up to 7 positions (Label: Rotating aperture wheel and filter wheel)
Interfaces	GigE, 10 GigE*, 2 \times CAMLink*, HDMI*
Trigger	4 IN / 2 OUT, TTL
Analogue signals*, IRIG-B*	2 IN / 2 OUT, yes
Tripod adapter	1/4" and 3/8" photo thread, 2 \times M5
Power supply	24 V DC, wide-range power supply (100 ... 240) V AC
Storage and operation temperature	(-40 ... 70) $^{\circ}\text{C}$, (-20 ... 50) $^{\circ}\text{C}$
Protection degree	IP54, IEC 60529
Dimensions; weight	(244 \times 120 \times 160) mm*; 4.0 kg (without lens)
Further functions	Multi Integration Time*, HDR, HighSense*
Analysis and evaluation software	IRBIS [®] 3, IRBIS [®] 3 view, IRBIS [®] 3 plus*, IRBIS [®] 3 professional*, IRBIS [®] 3 control*, IRBIS [®] 3 online*, IRBIS [®] 3 process*, IRBIS [®] 3 active*, IRBIS [®] 3 mosaic*, IRBIS [®] 3 vision*

* Depending on model

Lenses	Focal length (mm)	FOV ($^{\circ}$)	IFOV (mrad)
Wide-angle lens	13	(40.5 \times 32.9)	1.2
Standard lens	25	(21.7 \times 17.5)	0.6
Telephoto lens	50	(11.0 \times 8.8)	0.3
Telephoto lens	100	(5.5 \times 4.4)	0.15
Telephoto lens	200	(2.7 \times 2.2)	0.08



Observation of a person entering an area without authorisation



Thermal image of a drinking bat over a reflecting water surface

© InfraTec 02 / 2024 – All stated product names and trademarks remain in property of their respective owners. Design, specification and technical progress subject to change without prior notice.



Headquarters

InfraTec GmbH
Infrarotsensorik und Messtechnik
Gostritzer Straße 61 – 63
01217 Dresden / GERMANY

Phone +49 351 82876-610
E-mail thermo@InfraTec.de
www.InfraTec.eu

USA office

InfraTec infrared LLC
Phone +1 844-226-3722 (toll free)
E-mail thermo@InfraTec-infrared.com
www.InfraTec-infrared.com